Prisma

Slim LED luminaire with curved prismatic diffuser for surface mounting

- Through wiring (TW) variants available
- Robust and IP44 sealed housing extends applications to canteens, kitchens, laundry rooms, garages etc.
- Curved frosted (FR) prismatic diffuser for more visual comfort (wide light distribution, reduced glare)
- Highly efficient LED variants (up to 120 lm/W), sensor variants for even more energy saving
- Available in two lengths (600mm / 1200mm)

Photographs, line drawings and photometric data are representative only. For specific product detail please select an individual product.







96630837

Material/Finish
Body: Pre-painted white 0.7mm galvanised steel.
Endcaps: Shockproof ASA plastic, white.
Diffuser: Prismatic acrylic.

Installation/Mounting
Keyhole fixing positions Ø14mm for direct mounting to ceiling, wall or via bracket. Fixing centres: 500mm (600mm fixture). Two cable entries Ø19mm in the centre of the body and a knockout hole in the endcaps. Grommets included. Cable capacity 3 x 2 x 2.5mm².

Ordering Guide Lamps to be ordered separately, except where stated (L830/L840)

Description	ILCOS Code	Socket	Wt (kg)	SAP Code	Cat. No.
Prisma					
PRISMA LED3000-840 HF FR L600	LED		1,502	96630824	E7273328
PRISMA LED4400-840 HF FR L1200	LED		2,721	96630825	E7273329
PRISMA LED6200-840 HF FR L1200	LED		2,721	96630826	E7273330
PRISMA LED3000-830 HF FR L600	LED		1,502	96630830	E7273334
PRISMA LED4400-830 HF FR L1200	LED		2,721	96630831	E7273335
PRISMA LED6200-830 HF FR L1200	LED		2,721	96630832	E7273336
Prisma, through wired					

IP44, Beam_Surface_3, IK06, Beam_eControl_A, SC1, Beam_Emergency, CE, T16, 650, 850

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting

Prisma

Description	ILCOS Code	Socket	Wt (kg)	SAP Code	Cat. No.
PRISMA LED3000-840 HF FR L600 TW	LED		1,516	96630827	E7273331
PRISMA LED4400-840 HF FR L1200 TW	LED		2,811	96630828	E7273332
PRISMA LED6200-840 HF FR L1200 TW	LED		2,811	96630829	E7273333
PRISMA LED3000-830 HF FR L600 TW	LED		1,516	96630833	E7273337
PRISMA LED4400-830 HF FR L1200 TW	LED		2,811	96630834	E7273338
PRISMA LED6200-830 HF FR L1200 TW	LED		2,811	96630835	E7273339
Prisma, dimmable					
PRISMA LED3000-840 HFIX FR L600	LED		1,502	96630836	E7273340
PRISMA LED4400-840 HFIX FR L1200	LED		2,721	96630837	E7273341
PRISMA LED6200-840 HFIX FR L1200	LED		2,721	96630838	E7273342
PRISMA LED3000-830 HFIX FR L600	LED		1,502	96630842	E7273346
PRISMA LED4400-830 HFIX FR L1200	LED		2,721	96630843	E7273347
PRISMA LED6200-830 HFIX FR L1200	LED		2,721	96630844	E7273348
Prisma, dimmable, through wired					
PRISMA LED3000-840 HFIX FR L600 TW	LED		1,516	96630839	E7273343
PRISMA LED4400-840 HFIX FR L1200 TW	LED		2,811	96630840	E7273344
PRISMA LED6200-840 HFIX FR L1200 TW	LED		2,811	96630841	E7273345
PRISMA LED3000-830 HFIX FR L600 TW	LED		1,516	96630845	E7273349
PRISMA LED4400-830 HFIX FR L1200 TW	LED		2,811	96630846	E7273350
PRISMA LED6200-830 HFIX FR L1200 TW	LED		2,811	96630847	E7273366
Prisma, sensor versions					
PRISMA LED4400-830 HF FR MWS L1200	LED		2,735	96630848	E7273367
PRISMA LED4400-840 HF FR MWS L1200	LED		2,735	96630849	E7273368

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting