

## IQ Beam

96635109 IQ BEAM 4300-830 MPT-F HF Q600 TBL3

|                           |  |      |      |  |    |  |  |        |                           |
|---------------------------|--|------|------|--|----|--|--|--------|---------------------------|
| IEC EN<br>60598-1<br>RG 1 |  | IP20 | IK03 |  | CE |  |  | 650 °C | T <sub>a</sub> -20<br>+40 |
|---------------------------|--|------|------|--|----|--|--|--------|---------------------------|

### IQ Beam

A linear optic, recessed modular LED luminaire for exposed T, plasterboard and concealed grid ceilings. Fixed output, LED driver. Class I electrical, IP20, Impact strength: IK03. Body: white painted steel. Diffuser: micro prism structure acrylic with diffusing foil. Suitable for lay-in installation, pull up installation optional. Luminaire with internal connecting terminal, compatible with LINECT® outside connection. Complete with 3000K LED.

Dimensions: 597 x 597 x 60 mm  
 Luminaire input power: 32.2 W  
 Luminaire luminous flux: 4100 lm  
 Luminaire efficacy: 127 lm/W  
 Weight: 4.14 kg



TLG\_IQBM\_F\_pers\_B.jpg



TLG\_IQBM\_M\_LDQN.wmf

This product contains a light source of energy efficiency class C.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
 © Thorn Lighting

# **IQ Beam**

**96635109 IQ BEAM 4300-830 MPT-F HF Q600 TBL3**

**THORN**