

IQ Wave SP

THORN

E7016831 / 96629308 IQ SUSP S LED4250-830 HFIX HU SWD ML3

IP20	IK05					650°C	T _a -20 +25
------	------	---	---	---	---	-------	---------------------------

IQ Wave SP

A lightweight, Suspended, LED luminaire with MV Tech optic with higher upward light. Electronic, DALI dimmable control gear. Equipped with pull cord dimming switch. Class I electrical, IP20, IK05. Body, diffuser, frame and endcaps: polycarbonate finished in white (close to RAL9016). Gear tray: pre-coated white steel. Fitted with 3 core cable of 2, 5m length. Suspension wires included. Ceiling rose to be ordered separately. Complete with 3000K LED

Dimensions: 1165 x 210 x 70 mm

Luminaire input power: 40 W


Luminaire luminous flux: 4000 lm

Luminaire efficacy: 100 lm/W

weight: 4.5 kg



TLG_IQSU_F_SUS_PDB.jpg



TLG_IQSU_M_SUS.wmf

This product contains a light source of energy efficiency class C.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at $\pm 10\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting