# PopPack

## 96631567 POPPACK LED 6500-840 HF E3 L1800

IP20 | IK03 | 650 °C | $T_a$ 0 +25

## PopPack

Batten LED luminaire. Electronic, fixed output control gear with 3 hour, manual test, emergency lighting circuit. Body: coated, formed steel, white (RAL9016). End caps: injection moulded polycarbonate, white. Diffuser: textured opal acrylic. Electrical connection via (3 + 3) x 2 x 2.5mm² terminal block.  Complete with 4000K LED

Dimensions: 1728 x 60 x 74 mm
Luminaire input power: 54 W
Luminaire luminous flux: 6800 lm
Luminaire efficacy: 126 lm/W
Weight: 2.5 kg

TLG_POPL_F_PDB_EMPTY.jpg




TLG_POPL_M_LD1.wmf

This product contains a light source of energy efficiency class D.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime.  International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting