

96631893 VO 12L70-740 SF WSC CL1 W5 T60 ANT



## Volupto

A smart, post top LED lantern with a Wide Street & Comfort distribution. Programmable LED driver with 12 LEDs driven at 700mA. Class I electrical, IP66, IK10. Canopy and base: corrosion resistant die-cast powder coated aluminium, finished textured anthracite (close to RAL7043). Enclosure: UV stabilised polycarbonate. Complete with 4000K LED. Pre-wired with 5m cable. Post top mounting to Ø60mm column.

Dimensions: Ø60/406 x 571 mm  
 Luminaire input power: 26.3 W  
 Luminaire luminous flux: 3676 lm  
 Luminaire efficacy: 140 lm/W  
 Weight: 7.53 kg  
 Scx: 0.143 m<sup>2</sup>



TLG\_VOLU\_F\_Side.jpg



TLG\_VOLU\_M\_60.wmf

This product contains a light source of energy efficiency class D.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

**Volupto**

**96631893 VO 12L70-740 SF WSC CL1 W5 T60 ANT**

**THORN**