

IQ Wave SP

THORN

92906000 IQ SUSP S LED4900-840 HF HU SWD ML3 WH

IP20	IK05	⊕	CE			650°C	T _a -20 +25
------	------	---	----	--	--	-------	---------------------------

IQ Wave SP

A lightweight, Suspended, LED luminaire with MV Tech optic with higher upward light. Electronic, fixed output control gear. Equipped with dimming switch. Class I electrical, IP20, IK05. Body, diffuser, frame and endcaps: polycarbonate finished in white (close to RAL9016). Gear tray: pre-coated white steel. Fitted with 3 core cable of 2, 5m length. Suspension wires included. Ceiling rose to be ordered separately. Complete with 4000K LED

Dimensions: 1140 x 210 x 70 mm


Luminaire input power: 42 W

Luminaire luminous flux: 4900 lm

Luminaire efficacy: 117 lm/W



TLG_IQSU_F_SUS_PDB.jpg



TLG_IQSU_M_SUS.wmf

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at $\pm 10\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting

IQ Wave SP

92906000 IQ SUSP S LED4900-840 HF HU SWD ML3 WH

THORN