## **Victor**



## 96276873 VIC2 60L35-740 NR BP 3550 HFX CL2 ->




## Victor

A large size LED road and street luminaire, in a modern and timeless design. 60 LEDs driven at 350mA with Narrow Road optic. DALI dimmable LED driver. Class II electrical, IP66. Body in aluminium, powder coated Traffic white RAL9016. Enclosure: toughened flat glass. Luminaire to be suspended using brackets (Ø27G), post top, or wall mounted. Tool-free electrical connection via 2 x 2.5 mm<sup>2</sup> terminal block. Equipped with 50% power reduction circuit, effective 3 hours before and 5 hours after a calculated midnight. Pre-wired with 10m, 4 core cable. Complete with 4000K LED

Dimensions: Ø503 x 360 mm Luminaire input power: 63 W

Weight: 9.7 kg Scx: 0.144 m<sup>2</sup>





TLG\_VCTR\_M\_SWLD2.wmf

This product contains light sources of energy efficiency class D.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

## **Victor**



96276873 VIC2 60L35-740 NR BP 3550 HFX CL2 ->