

## 96633073 DUROLIGHT-C 3600-840 HF L1215

IP65	IK10					850°C		T <sub>a</sub> -25 +45
------	------	--	--	--	--	-------	--	---------------------------


### Durolight

Anti-vandal Surface mounted cornice LED luminaire.  
 Electronic, fixed output control gear. IP65, IK10, Class I electrical. Body: 2mm sheet steel painted white (close to RAL9016). Gasket: non-ageing polyurethane foam.  
 Diffuser: 3mm thick polycarbonate with outstanding impact resistance, connected and secured with tamper-resistant stainless steel twin hole screws to the body. Complete with 4000K LED

Dimensions: 1215 x 175 x 175 mm  
 Luminaire input power: 38 W  
 Luminaire luminous flux: 3589 lm  
 Luminaire efficacy: 94 lm/W  
 Weight: 11 kg



TLG\_DURO\_F\_CORNER.jpg



TLG\_DURO\_M\_LDC.wmf

This product contains a light source of energy efficiency class C.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

**Durolight**

**96633073 DUROLIGHT-C 3600-840 HF L1215**

**THORN**