

IP65	IK10					850°C		170Nm		T _a -25 +45
------	------	--	--	--	--	-------	--	-------	--	---------------------------


Durolight

Anti-vandal Surface mounted cornice LED luminaire.
 Electronic, fixed output control gear with 3 hour, manual test, emergency lighting circuit. IP65, IK10, Class I electrical. Body: 2mm sheet steel painted white (close to RAL9016). Gasket: non-ageing polyurethane foam. Diffuser: 3mm thick polycarbonate with outstanding impact resistance, connected and secured with tamper-resistant stainless steel twin hole screws to the body. Complete with 3000K LED

Dimensions: 1215 x 175 x 175 mm
 Luminaire input power: 37.6 W
 Luminaire luminous flux: 3454 lm
 Luminaire efficacy: 92 lm/W
 Weight: 11 kg



TLG_DURO_F_CORNER.jpg



TLG_DURO_M_LDC.wmf

This product contains a light source of energy efficiency class C.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Durolight

96633083 DUROLIGHT-C 3500-830 HF E3 L1215

THORN