







# Omega Pro 2

THORN

E7018070 / 92913995 OP2 4400-830 HX HFIX Q600

IEC EN 60598-1 RG 0				IK03				650°C	T <sub>a</sub> 0 +35
---------------------------	---	---	---	------	---	---	---	-------	-------------------------


## Omega Pro 2

A recessed/surface/suspended, edge-lit LED luminaire.  
LED driver, DALI-2 dimmable. Class II electrical,  
IP40\_IP20, Impact strength: IK03. Body: sheet steel,  
finished white (close to RAL9016). Diffuser: UV-stabilised  
polycarbonate hexagonal comfort optic. Electrical  
connection via piano key terminals, loop-in/loop-out  
possible. Complete with 3000K LED, Colour Rendering  
Index min.: 80

Dimensions: 597 x 597 x 55 mm  
Luminaire input power: 32.9 W  
Luminaire luminous flux: 4150 lm  
Luminaire efficacy: 126 lm/W  
Weight: 5.05 kg



TLG\_OMP2\_F\_QH\_PDB.jpg



TLG\_OMP2\_M\_Q.wmf

This product contains a light source of energy efficiency class E.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at  $\pm 10\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting