## Voyager Style



## 96632896 VOYAGER STYLE 115 P MS ECD SM-S WH


IP43 | IK03 | **C** 

## Voyager Style

Ultra slim LED escape sign luminaire for surface mounted, wall or ceiling mounting; recessed ceiling mounting possible with optional recessed ceiling frame; Luminaire for central emergency light supply, for single luminaire monitoring via DALI (DALI-2 certified), settable emergency light level; Non-maintained and maintained mode settable via the central battery system; housing made of polycarbonate; luminaire easy to install; Quick fit terminal block, through wiring possible up to 2,5 mm<sup>2</sup>; supplied with a set of ISO 7010 mountable direction signs (left, right, up, down and blank) for viewing from a maximum distance of 23 m; mounting of signs with discrete mounting pins; zero maintenance thanks to LED technology; service life of 50, 000 h at constant luminous flux; uniform backlighting of pictogram; luminance > 500 cd/m² in the white region; Power supply: 220/240 V AC; Luminaire input power: 2.8 W; degree of protection: IP43, class of protection: Class II electrical; Impact strength: Impact strength: IK03; Dimensions: 265 x 37 x 191 mm; weight: 0.75 kg



TLG VYST F 115MS.jpg



TLG\_VYST\_M\_115MFS.wmf