

# Omega Pro 2

92915522 OP2 3000-830 OP HF Q600

THORN

IEC EN 60598-1 RG 0					650 °C
---------------------------	---	---	---	---	--------

## Omega Pro 2

A recessed/surface/suspended, edge-lit LED luminaire.  
LED driver, Fixed output. Class II electrical, IP44\_IP20,  
Impact strength: IK03. Body: sheet steel, finished white  
(close to RAL9016). Diffuser: UV-stabilised  
polymethylmethacrylate opal optic for wide light distribution.  
Electrical connection via piano key terminals, loop-in/loop-  
out possible. Complete with 3000K LED, Colour Rendering  
Index min.: 80

Dimensions: 597 x 597 x 55 mm  
Luminaire input power: 24.4 W  
Luminaire luminous flux: 2650 lm  
Luminaire efficacy: 109 lm/W  
Weight: 5.05 kg



TLG\_OMP2\_F\_QO\_PDB.jpg



TLG\_OMP2\_M\_Q.wmf

This product contains a light source of energy efficiency class E.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at  $\pm 10\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting