

# Equaline

96633615 EQL CL C L791 PM SRE

THORN



## Equaline

Equaline frameless (CL) channel with optics for 2nd generation Equaline. Body: silver powder coated, suitable for surface, suspended and plasterboard installation. For single and continuous installation. Optics: (PM) made of PMMA. Batten, end cap set and installation accessories to be ordered separately. Luminaire wired with halogen free leads.

Equaline consists of a channel, LED-batten, cover and accessories, which have to be configured and ordered separately. This product is one part of the complete configuration.

Dimensions: 791 x 791 x 88 mm  
Weight: 3.2 kg



TLG\_EQUL\_F\_corner\_pers.jpg



TLG\_EQUL\_M\_surface\_suspended\_plasterboard.wmf

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at  $\pm 10\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting

**Equaline**

**96633615 EQL CL C L791 PM SRE**

**THORN**