7216304 / 96634331 <HIPAK LED10000-840 HFI-X WD GEN3 HE

IP65 | D | IK08 | 850°C | T_a -30 +50

An IP65 single point suspension LED high bay luminaire with wide beam optic. DALI dimmable LED driver, for 220-240V, 50/60Hz supply. Class I electrical. IK08. Housing: die-cast aluminium. Lens/Diffuser: polycarbonate. Supplied with mounting hook. Equipped with quick fit electrical connection. Complete with 4000K LED.

Dimensions: Ø320 x 143 mm
Luminaire input power: 65 W
Luminaire luminous flux: 10510 lm
Luminaire efficacy: 162 lm/W
Weight: 3.15 kg

TLG_HIPK_F_3SPERS.jpg



TLG_HIPK_M_3S.wmf

This product contains a light source of energy efficiency class C.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting