

Beta 3

THORN

E7019565 / 96634501 BETA 3 4100-830 HFIX LRO Q600

IEC EN 60598-1 RG 0	↓ IP20 ↑ IP44	IK03		CE				650 °C	T _a -20 +40	
---------------------------	------------------	------	--	----	--	--	--	--------	---------------------------	--

Beta 3


A square ceiling recessed LED luminaire. DALI dimmable LED driver. Class II electrical, IP44_IP20, Impact strength: IK03. Body: sheet steel, white (close to RAL9016). Diffuser: Opalised PMMA with micro-prismatic foil inlay. Supplied with safety wire. Complete with 3000K LED.

UGR < 19 and L65 < 3000 cd/m² as per EN 12464

Dimensions: 596 x 596 x 34 mm
Luminaire input power: 33.6 W
Luminaire luminous flux: 3690 lm
Luminaire efficacy: 110 lm/W
Weight: 2.11 kg



TLG_BET3_F_MREQ.jpg



TLG_BET3_M_Q600.wmf

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at $\pm 10\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting

Beta 3

E7019565 / 96634501 BETA 3 4100-830 HFIX LRO Q600

THORN