

## Beta 3

THORN

### 96635140 BETA 3 4100-840 HFIX E3 LRO Q600

IEC EN 60598-1 RG 0			IK03					650°C	T <sub>a</sub> 0 +25	
---------------------------	---	---	------	---	---	---	---	-------	-------------------------	--

#### Beta 3


A square ceiling recessed LED luminaire. DALI dimmable LED driver with 3 hour, manual test, emergency lighting circuit. Class I electrical, IP44 IP20, Impact strength: IK03. Body: sheet steel, white (close to RAL9016). Diffuser: Opalised PMMA with micro-prismatic foil inlay. Supplied with safety wire. Complete with 4000K LED.

UGR < 19 and L65 < 3000 cd/m<sup>2</sup> as per EN 12464

Dimensions: 596 x 596 x 34 mm  
Luminaire input power: 33.6 W  
Luminaire luminous flux: 4100 lm  
Luminaire efficacy: 122 lm/W  
Weight: 3.71 kg



TLG\_BET3\_F\_MREQ.jpg



TLG\_BET3\_M\_Q600.wmf

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at  $\pm 10\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting