

96635457 TR 36L50-740 NR CL2 FD T60E ANT

ISO 9223 C5		IP66 IK10				T _a 25
----------------	---	-----------	---	---	---	-------------------


Thor

A small size, smart urban LED lantern with 36 LEDs driven at 500mA with narrow road optic and die-cast aluminium EN AC 47100 + CAT dome with anthracite finish (close to RAL7043). Class II electrical, IP66, IK10. Body: die-cast aluminium (EN AC 47100 + CAT) treated against corrosion, powder coated anthracite (close to RAL7043), bracket: die-cast aluminium (EN AC-47100 + CAT) treated against corrosion, powder coated anthracite (close to RAL7043). Enclosure: 6mm toughened flat glass. Screws and closing set: stainless steel. Post top mounting to Ø60mm column, tilt 0°, adjustable from -15° to +10°. Complete with 4000K LED.

Dimensions: 618 x 459 x 251 mm
 Luminaire input power: 55 W
 Luminaire luminous flux: 8454 lm
 Luminaire efficacy: 154 lm/W
 Weight: 8.95 kg
 Scx: 0.038 m²



TLG_THOR_F_SMTFPD.jpg



TLG_THOR_M_MTP.wmf

This product contains a light source of energy efficiency class E.

Thor

96635457 TR 36L50-740 NR CL2 FD T60E ANT

THORN