

# Punch

# THORN

E7021431 / 96635476 PUNCH 3 LV MSP 5500-930 L12 HFIX SWD

UK CA	IP20	IK03	⊕	CE			650°C	T <sub>a</sub> 0 +25
----------	------	------	---	----	--	--	-------	-------------------------

## Punch


A slim, suspended luminaire with direct/indirect distribution. DALI dimmable Electronic,. Body: sheet steel, powder coated white (close to RAL9016). Endcaps: sheet steel powder coated white (close to RAL9016). Louvre: glossy aluminium,. Class I electrical, IP20, Impact strength: IK03. Electrical connection via pre-installed power cord (2.5m). Complete with 3000K LED. Equipped with pull cord dimming switch. Suspension kit to be ordered separately.

Y-Suspension connector included - Suspension cord with ceiling rose to be ordered separately (22171581).

Dimensions: 1301 x 162 x 56 mm  
Luminaire input power: 42.3 W  
Luminaire luminous flux: 5404 lm  
Luminaire efficacy: 128 lm/W  
Weight: 3.5 kg



TLG\_PNCH\_F\_LOUVRE\_recessed\_on.jpg



TLG\_PNC3\_M\_LV\_RESD.wmf

This product contains light sources of energy efficiency class D.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting

**Punch**

**E7021431 / 96635476 PUNCH 3 LV MSP 5500-930 L12 HFIX SWD**

**THORN**