

Novaline Style

96635527 NOVS S 1900-840 DI HF E3 WH

| | | | | | | | | | | | | |
|---------------------------|------|----------|------|--|---------|------|--|----|--|--|-------|-------------------------|
| IEC EN 60598-1 RG 1 | RoHS | UK CA | IP54 | | halogen | IK08 | | CE | | | 850°C | T _a 0 +25 |
|---------------------------|------|----------|------|--|---------|------|--|----|--|--|-------|-------------------------|

Novaline Style

Decorative circular luminaire with small body. Low indirect component for wall and ceiling illumination. Electronic, fixed output control gear with 3 hour, manual test, emergency lighting circuit. Aesthetic trim of the luminaire made of polycarbonate in white. Diffuser: opal polycarbonate. Class II electrical, IP54. Complete with 4000K LED.

Dimensions: Ø320 x 69 mm
 Luminaire input power: 13.2 W
 Luminaire luminous flux: 1900 lm
 Luminaire efficacy: 144 lm/W
 Weight: 1.94 kg



TLG_NOVS_F_3WH.jpg



TLG_NOVS_M_LD300.wmf

This product contains a light source of energy efficiency class C.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Novaline Style

96635527 NOVS S 1900-840 DI HF E3 WH

THORN