

92948106 CETUS3 M 3000-830 HFIX RSB

IEC EN 60598-1 RG 1	UK CA			halogen	IK 06		CE		850°C	T _a -20 +25	
---------------------------	----------	--	--	---------	-------	--	----	--	-------	---------------------------	--


Cetus

A low height, recessed LED downlight. Suitable for ceiling cut-outs Ø145-180 mm for easy refurbishments or fast initial installations. Remote, pluggable, DALI dimmable LED driver with DC functionality, adjustable 15-100%, NFC configurable, SwitchDIM compatible. Loop in - loop out possible. Body: die-cast aluminium for thermal management. Diffuser: polycarbonate, smooth reflector in satinbrite finish with wide beam. Reflector and trim: high quality, highly reflective polycarbonate. Class II electrical, IP44_IP20. Spring clips suitable for ceiling thicknesses from 1 to 35 mm. Complete with 3000K LED

Dimensions: Ø195 x 100 mm
 Luminaire input power: 26.9 W
 Luminaire luminous flux: 3023 lm
 Luminaire efficacy: 112 lm/W
 Weight: 0.7 kg



TLG_CTU3_F_M_LED_RSB_Persp.jpg



TLG_CTU3_M_HFM.wmf

This product contains a light source of energy efficiency class D.