

## Punch

96635716 PUNCH 3 LV MSP 6600-940 L15 HFIX



### Punch


A slim, suspended luminaire with direct/indirect distribution. DALI dimmable Electronic,. Body: sheet steel, powder coated white (close to RAL9016). Endcaps: sheet steel powder coated white (close to RAL9016). Louvre: glossy aluminium,. Class I electrical, IP20, Impact strength: IK03. Electrical connection via pre-installed power cord (2.5m). Complete with 4000K LED. Suspension kit to be ordered separately.

Y-Suspension connector included - Suspension cord with ceiling rose to be ordered separately (22171581).

Dimensions: 1581 x 162 x 56 mm  
 Luminaire input power: 48 W  
 Luminaire luminous flux: 6560 lm  
 Luminaire efficacy: 137 lm/W  
 Weight: 3.5 kg



TLG\_PNCH\_F\_LOUVRE\_recessed\_on.jpg



TLG\_PNC3\_M\_LV\_RESD.wmf

This product contains light sources of energy efficiency class D.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

# Punch

96635716 PUNCH 3 LV MSP 6600-940 L15 HFIX

THORN