

Punch

THORN

96635728 PUNCH 3 LV MSC 4000-840 L12 HFIX E3

UK CA	IP20	IK03					650°C	T _a 0 +25	
----------	------	------	--	--	--	--	-------	-------------------------	--

Punch


A slim, surface mounted luminaire with direct distribution.
DALI dimmable Electronic, with 3 hour, manual test,
emergency lighting circuit. Body: sheet steel, powder
coated white (close to RAL9016). Endcaps: sheet steel
powder coated white (close to RAL9016). Louvre: glossy
aluminium,. Class I electrical, IP20, Impact strength: IK03.
Electrical connection via piano key terminal block.
Complete with 4000K LED.

Can be used as a suspended direct only luminaire when
combined with Y-Suspension connector and suspension kit
(to be ordered separately 22171581 & 22171349).

Dimensions: 1301 x 162 x 56 mm
Luminaire input power: 29 W
Luminaire luminous flux: 4120 lm
Luminaire efficacy: 142 lm/W
Weight: 3.5 kg



TLG_PNCH_F_LOUVRE_surface_on.jpg



TLG_PNC3_M_LV_RESD.wmf

This product contains a light source of energy efficiency class C.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at $\pm 10\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting