### **Victor**



#### 96635791 VIC1 24L50-740 NR CL2 N8M R9006




#### Victor

A small size LED road and street luminaire, in a modern and timeless design. 24 LEDs driven at 500mA with Narrow Road optic. Fixed output LED driver. Class II electrical, IP66. Body in aluminium, powder coated White aluminium RAL9006. Enclosure: toughened glass. Luminaire to be suspended using brackets (Ø27G), post top, or wall mounted. Tool-free electrical connection via 2 x 2.5 mm<sup>2</sup> terminal block. Pre-wired with 8m H07-RNF cable. Complete with 4000K LED

Dimensions: Ø363 x 277 mm Luminaire input power: 38 W

Weight: 4.84 kg Scx: 0.084 m<sup>2</sup>





TLG\_VCTR\_M\_SWLD1.wmf

This product contains a light source of energy efficiency class D.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

## Victor

# **THORN**

96635791 VIC1 24L50-740 NR CL2 N8M R9006