

| | | | | | | | | | |
|----------|------|------|---|----|----|----|-------|-------------------------|--|
| UK CA | IP20 | IK03 | ⏚ | CE | ⚙️ | ⚙️ | 650°C | T _a 0 +25 | |
|----------|------|------|---|----|----|----|-------|-------------------------|--|

Punch

A slim, suspended luminaire with direct/indirect distribution. fixed output control gear Electronic,. Body: sheet steel, powder coated white (close to RAL9016). Endcaps: sheet steel powder coated white (close to RAL9016). Louvre: glossy aluminium,. Class I electrical, IP20, Impact strength: IK03. Electrical connection via piano key terminal block. Complete with 3000K LED.

Y-Suspension connector included - Suspension cord with ceiling rose to be ordered separately (22171581).

Dimensions: 1581 x 162 x 56 mm
Luminaire input power: 48 W
Luminaire luminous flux: 6660 lm
Luminaire efficacy: 139 lm/W
Weight: 3.8 kg



TLG_PNCH_F_LOUVRE_recessed_on.jpg



TLG_PNC3_M_LV_RESD.wmf

This product contains light sources of energy efficiency class C.

Punch

E7023067 / 96636017 PUNCH 3 LV MSP 6600-830 L15 HF

THORN