

## IQ Beam

96636077 IQ BEAM HT 6300-840 MPT-F HFIX Q600

|                           |  |      |      |  |  |  |  |        |                           |
|---------------------------|--|------|------|--|--|--|--|--------|---------------------------|
| IEC EN<br>60598-1<br>RG 1 |  | IP20 | IK03 |  |  |  |  | 650 °C | T <sub>a</sub> -20<br>+50 |
|---------------------------|--|------|------|--|--|--|--|--------|---------------------------|

### IQ Beam

A linear optic, recessed modular LED luminaire for exposed T, plasterboard and concealed grid ceilings. DALI-2 dimmable, LED driver. Class I electrical, IP20, Impact strength: IK03. Body: white painted steel. Diffuser: micro prism structure acrylic with diffusing foil. Suitable for lay-in installation, pull up installation optional. Complete with 4000K LED.

Dimensions: 597 x 597 x 60 mm  
 Luminaire input power: 50 W  
 Luminaire luminous flux: 6300 lm  
 Luminaire efficacy: 126 lm/W  
 Weight: 4.26 kg



TLG\_IQBM\_F\_HT\_pers.jpg



TLG\_IQBM\_M\_HT\_P.wmf

This product contains a light source of energy efficiency class C.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.