

96636153 IS S 24L25-730 NR CL2 WS0.3 M60 GY-S

ISO 9223 C5	ida LANK SKY APPROVED	IP66	IK08		CE			T _a 50	
----------------	--------------------------	------	------	--	----	--	--	-------------------	--

Isaro

A discrete and flexible road and street lantern with durable high performance. Programmable LED driver, set for fixed output, driving 24 LEDs at 250mA. Body: small size, die-cast aluminium (EN AC-44300), powder coated textured Light grey textured (150) - partly painted. Shaft: Light grey textured (150) - partly painted/unpainted. Cover: Extra White glass. Fixings: stainless steel with anti-galvanic treatment. narrow road optic, with Colour Rendering Index min.: 70, Correlated colour temperature*: 3000 Kelvin LEDs supplied. Class II electrical, Impact strength: IK08, IP66, Ta max.: 50°C. Supplied with Ø60mm spigot adaptor which can be fitted for post-top (0°/5°/10° tilt) or side-entry (-20°/-15°/-10°/-5°/0° tilt). Pre-wired with 0.3m, 1.5mm² H07RN-F cable.

Dimensions: 550 x 238 x 157 mm

Luminaire input power: 19 W

Luminaire luminous flux: 2960 lm


Luminaire efficacy: 156 lm/W

Weight: 4 kg

Scx: 0.041 m²



TLG_ISLC_F_S_ZU_SR.jpg



TLG_ISLC_M_SMTP60.wmf

This product contains a light source of energy efficiency class D.

Isaro

96636153 IS S 24L25-730 NR CL2 WS0.3 M60 GY-S

THORN