

Chalice 3

THORN

E7477387 / 96108669 CHAL3 MSF180 1400-840 EHF RSB

IEC EN 60598-1 RG 1	UK CA	IP43	halogen	IK06	⏏	CE	⚡	⚡	850°C	T _a 25	
---------------------------	----------	------	---------	------	---	----	---	---	-------	-------------------	--


Chalice 3

A high efficient and sustainable, surface mounted LED downlight. Fixed output LED driver with DC functionality, fixed at 100%. Body: die-cast aluminium. Diffuser: polycarbonate, smooth reflector in satinbrite finish with wide beam. Trim: high quality, highly reflective polycarbonate. Class I electrical, IP43. Installation plate to be fitted directly to ceiling, for mounting via BESA box or wire suspension use available accessory. Electrical connection via 3/5 pole, push in, terminal block, Housing mounts to installation plate with twist and lock bayonet mechanism. Complete with 4000K LED

Dimensions: Ø180 x 182 mm
Luminaire input power: 12.1 W
Luminaire luminous flux: 1400 lm
Luminaire efficacy: 116 lm/W
Weight: 2.67 kg



TLG_CHAL3_F_180MSF_RSB.jpg



TLG_CHAL3_M_MS180.wmf

This product contains a light source of energy efficiency class C.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at $\pm 10\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting