

# Chalice 3

THORN

E7477388 / 96108672 CHAL3 MSF125 800-840 EHF RSB

IEC EN 60598-1 RG 1	UK CA	IP43	halogen	IK06	⏚	CE	⚡	⚡	850°C	T <sub>a</sub> 25	
---------------------	-------	------	---------	------	---	----	---	---	-------	-------------------	--


## Chalice 3

A high efficient and sustainable, surface mounted LED downlight. Fixed output LED driver with DC functionality, fixed at 100%. Body: die-cast aluminium. Diffuser: polycarbonate, smooth reflector in satinbrite finish with wide beam. Trim: high quality, highly reflective polycarbonate. Class I electrical, IP43. Installation plate to be fitted directly to ceiling, for mounting via BESA box or wire suspension use available accessory. Electrical connection via 3/5 pole, push in, terminal block, Housing mounts to installation plate with twist and lock bayonet mechanism. Complete with 4000K LED

Dimensions: Ø125 x 126 mm  
Luminaire input power: 7.3 W  
Luminaire luminous flux: 782 lm  
Luminaire efficacy: 107 lm/W  
Weight: 1.19 kg



TLG\_CHAL3\_F\_125MSF\_RSB.jpg



TLG\_CHAL3\_M\_MS125.wmf

This product contains a light source of energy efficiency class C.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at  $\pm 10\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting

## Chalice 3

E7477388 / 96108672 CHAL3 MSF125 800-840 EHF RSB

THORN