

Chalice 3

92989211 CHAL3 150 3000-840 EHF RMB

IEC EN 60598-1 RG 1	UK CA	IP20	halogen	IK09	CE	850°C	Ta25	
---------------------	-------	------	---------	------	----	-------	------	--

Chalice 3


A highly efficient and sustainable LED downlight with low height. Suitable for mounting in ceiling thicknesses of 1 to 40 mm and Ø150mm cut-out with spring clips. Remote, pluggable, Fixed output LED driver with DC functionality, adjustable 50-100%, NFC configurable. Loop in - loop out possible. Body: die-cast aluminium for highly efficient thermal management with recycling content >90%. Diffuser: polycarbonate. Reflector and trim: polycarbonate smooth reflector in high glossy finish for improved glare control in office applications. Class II electrical, IP54_IP20. Complete with 4000K LED

Installation in concrete ceilings not permitted.

Dimensions: Ø174 x 94 mm
 Luminaire input power: 27.5 W
 Luminaire luminous flux: 3343 lm
 Luminaire efficacy: 122 lm/W
 Weight: 0.68 kg



TLG_CHAL3_F_150_RMB_IP54.jpg



TLG_CHAL3_M_EHF150.wmf

This product contains a light source of energy efficiency class B.

Chalice 3

92989211 CHAL3 150 3000-840 EHF RMB

THORN