

Chalice 3

92989215 CHAL3 150 1400-840 HFIX RSB

| | | | | | | | | | | | | |
|------------------------|----------|--|--|--|------|--|--|--|--|-------|-------------------|--|
| IEC EN 60598-1 RG 1 | UK CA | | | | IK09 | | | | | 850°C | T _a 25 | |
|------------------------|----------|--|--|--|------|--|--|--|--|-------|-------------------|--|

Chalice 3

A highly efficient and sustainable LED downlight with low height. Suitable for mounting in ceiling thicknesses of 1 to 40 mm and Ø150mm cut-out with spring clips. Remote, pluggable, DALI-2 dimmable LED driver with DC functionality, adjustable 15-100%, NFC configurable, SwitchDIM compatible. Loop in - loop out possible. Body: die-cast aluminium for highly efficient thermal management with recycling content >90%. Diffuser: polycarbonate. Reflector and trim: polycarbonate smooth reflector in satinbrite finish with wide beam. Class II electrical, IP54_IP20. Complete with 4000K LED

Dimensions: Ø174 x 94 mm
 Luminaire input power: 12.2 W
 Luminaire luminous flux: 1390 lm
 Luminaire efficacy: 114 lm/W
 Weight: 0.69 kg



TLG_CHAL3_F_150_RSB.jpg



TLG_CHAL3_M_EHF150.wmf

This product contains a light source of energy efficiency class C.

Chalice 3

92989215 CHAL3 150 1400-840 HFIX RSB

THORN