

## Chalice 3

92989219 CHAL3 150 2000-830 HFIX RMB

IEC EN 60598-1 RG 1	UK CA	IP20	halogen	IK09	CE	850°C	T <sub>a</sub> 25	
---------------------	-------	------	---------	------	----	-------	-------------------	--


### Chalice 3

A highly efficient and sustainable LED downlight with low height. Suitable for mounting in ceiling thicknesses of 1 to 40 mm and Ø150mm cut-out with spring clips. Remote, pluggable, DALI-2 dimmable LED driver with DC functionality, adjustable 15-100%, NFC configurable, SwitchDIM compatible. Loop in - loop out possible. Body: die-cast aluminium for highly efficient thermal management with recycling content >90%. Diffuser: polycarbonate. Reflector and trim: polycarbonate smooth reflector in high glossy finish for improved glare control in office applications. Class II electrical, IP54\_IP20. Complete with 3000K LED

Dimensions: Ø174 x 94 mm  
 Luminaire input power: 16.7 W  
 Luminaire luminous flux: 2082 lm  
 Luminaire efficacy: 125 lm/W  
 Weight: 0.69 kg



TLG\_CHAL3\_F\_150\_RMB\_IP54.jpg



TLG\_CHAL3\_M\_EHF150.wmf

This product contains a light source of energy efficiency class C.