

## Chalice 3

92989236 CHAL3 200 1400-840 HFIX RSB

IEC EN 60598-1 RG 1	UK CA				halogen	IK09		CE				850°C	T <sub>a</sub> 25	
------------------------	----------	--	--	--	---------	------	--	----	--	--	--	-------	-------------------	--


### Chalice 3

A highly efficient and sustainable LED downlight with low height. Suitable for mounting in ceiling thicknesses of 1 to 40 mm and Ø200mm cut-out with spring clips. Remote, pluggable, DALI-2 dimmable LED driver with DC functionality, adjustable 15-100%, NFC configurable, SwitchDIM compatible. Loop in - loop out possible. Body: die-cast aluminium for highly efficient thermal management with recycling content >90%. Diffuser: polycarbonate. Reflector and trim: polycarbonate smooth reflector in satinbrite finish with wide beam. Class II electrical, IP54\_IP20. Complete with 4000K LED

Dimensions: Ø223 x 96 mm  
 Luminaire input power: 11.4 W  
 Luminaire luminous flux: 1460 lm  
 Luminaire efficacy: 128 lm/W  
 Weight: 0.94 kg



TLG\_CHAL3\_F\_200\_RSB.jpg



TLG\_CHAL3\_M\_EHF200.wmf

This product contains a light source of energy efficiency class C.

## Chalice 3

92989236 CHAL3 200 1400-840 HFIX RSB

THORN