

Chalice 3

THORN

E7477382 / 92996204 CHAL3 MSF125 800-830 EHF RSB




Chalice 3

A high efficient and sustainable, surface mounted LED downlight. Fixed output LED driver with DC functionality, fixed at 100%. Body: die-cast aluminium. Diffuser: polycarbonate, smooth reflector in satinbrite finish with wide beam. Trim: high quality, highly reflective polycarbonate. Class I electrical, IP43. Installation plate to be fitted directly to ceiling, for mounting via BESA box or wire suspension use available accessory. Electrical connection via 3/5 pole, push in, terminal block, Housing mounts to installation plate with twist and lock bayonet mechanism. Complete with 3000K LED

Dimensions: Ø125 x 126 mm
Luminaire input power: 7.3 W
Luminaire luminous flux: 750 lm
Luminaire efficacy: 103 lm/W
Weight: 1.19 kg



TLG_CHAL3_F_125MSF_RSB.jpg



TLG_CHAL3_M_MS125.wmf

This product contains a light source of energy efficiency class D.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting