

Chalice 3

93901199 CHAL3 150 3000-840 EHF E3D RMB

IEC EN 60598-1 RG 1	UK CA	IP20	halogen	IK09	CE	850°C	Ta25	
---------------------	-------	------	---------	------	----	-------	------	--

Chalice 3


A high efficient and sustainable LED downlight with low height. Suitable for mounting in ceiling thicknesses of 1 to 40 mm and Ø150mm cut-out with spring clips. Remote, pluggable, Fixed output LED driver NFC configurable with 3 hour, Self/DALI Addressable test, emergency lighting circuit. Body: die-cast aluminium for high efficient thermal management with recycling content >90%. Diffuser: polycarbonate. Reflector and trim: polycarbonate smooth reflector in high glossy finish for improved glare control in office applications. Class II electrical, IP54_IP20. Complete with 4000K LED

Installation in concrete ceilings not permitted.

Dimensions: Ø174 x 94 mm
 Luminaire input power: 30 W
 Luminaire luminous flux: 3343 lm
 Luminaire efficacy: 111 lm/W
 Weight: 1.13 kg



TLG_CHAL3_F_150_RMB_IP54_EMG.jpg



TLG_CHAL3_M_EHF150.wmf

Chalice 3

93901199 CHAL3 150 3000-840 EHF E3D RMB

THORN