

Chalice 3

93901264 CHAL3 150 1400-840 HFIX E3 RMB

IEC EN 60598-1 RG 1	UK CA				halogen	IK09		CE				850°C	T _a 25	
------------------------	----------	--	--	--	---------	------	--	----	--	--	--	-------	-------------------	--

Chalice 3

A high efficient and sustainable LED downlight with low height. Suitable for mounting in ceiling thicknesses of 1 to 40 mm and Ø150mm cut-out with spring clips. Remote, pluggable, DALI-2 dimmable LED driver NFC configurable, SwitchDIM compatible with 3 hour, manual test, emergency lighting circuit. Body: die-cast aluminium for high efficient thermal management with recycling content >90%. Diffuser: polycarbonate. Reflector and trim: polycarbonate smooth reflector in high glossy finish for improved glare control in office applications. Class II electrical, IP54_IP20. Complete with 4000K LED

Dimensions: Ø174 x 94 mm
 Luminaire input power: 15.1 W
 Luminaire luminous flux: 1481 lm
 Luminaire efficacy: 98 lm/W
 Weight: 1.14 kg



TLG_CHAL3_F_150_RMB_IP54_EMG.jpg



TLG_CHAL3_M_EHF150.wmf

This product contains a light source of energy efficiency class C.

Chalice 3

93901264 CHAL3 150 1400-840 HFIX E3 RMB

THORN