

Chalice 3

93901303 CHAL3 200 1400-830 EHF E3D RSB




Chalice 3

A high efficient and sustainable LED downlight with low height. Suitable for mounting in ceiling thicknesses of 1 to 40 mm and Ø200mm cut-out with spring clips. Remote, pluggable, Fixed output LED driver NFC configurable with 3 hour, Self/DALI Addressable test, emergency lighting circuit. Body: die-cast aluminium for high efficient thermal management with recycling content >90%. Diffuser: polycarbonate. Reflector and trim: polycarbonate smooth reflector in satinbrite finish with wide beam. Class II electrical, IP54_IP20. Complete with 3000K LED

Dimensions: Ø223 x 96 mm
 Luminaire input power: 14.4 W
 Luminaire luminous flux: 1400 lm
 Luminaire efficacy: 97 lm/W
 Weight: 1.39 kg



TLG_CHAL3_F_200_RSB_EM.jpg



TLG_CHAL3_M_EHF200.wmf

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.