

Chalice 3

93901357 CHAL3 150 2000-840 EHF E3D RSB

IEC EN 60598-1 RG 1	UK CA				halogen	IK09		CE			850°C	T _a 25	
---------------------	-------	--	--	--	---------	------	--	----	--	--	-------	-------------------	--

Chalice 3

A high efficient and sustainable LED downlight with low height. Suitable for mounting in ceiling thicknesses of 1 to 40 mm and Ø150mm cut-out with spring clips. Remote, pluggable, Fixed output LED driver NFC configurable with 3 hour, Self/DALI Addressable test, emergency lighting circuit. Body: die-cast aluminium for high efficient thermal management with recycling content >90%. Diffuser: polycarbonate. Reflector and trim: polycarbonate smooth reflector in satinbrite finish with wide beam. Class II electrical, IP54_IP20. Complete with 4000K LED

Dimensions: Ø174 x 94 mm
Luminaire input power: 19.7 W
Luminaire luminous flux: 2040 lm
Luminaire efficacy: 104 lm/W
Weight: 1.13 kg



TLG_CHAL3_F_150_RSB_EM.jpg



TLG_CHAL3_M_EHF150.wmf

This product contains a light source of energy efficiency class B.

Chalice 3

93901357 CHAL3 150 2000-840 EHF E3D RSB

THORN