



Isaro

Discrete and flexible road and street lighting lantern with durable high performance

- IDA Dark Sky Approved
- *IDA fixture seal of approval relates to ≤ 3000 K only and clear enclosures, $\pm 10^\circ$ maximum tilt only. Luminaires must be mounted as photometered.
- Designed to maximize lighting performances, optimize circular economy strategies, while limiting its carbon footprint.
- Reliable and flexible : high quality die-cast aluminium EN AC 44300 casting and Geomet anti-galvanic treated screws combined with vast range of lighting distributions, control, protection, wiring and color options
- Highest corrosion protection according to EN ISO 9223 : Class 5
- Light weight, pre-wired to the needs for easy installation



Photographs, line drawings and photometric data are representative only. For specific product detail please select an individual product.



96634794

Material/Finish

Housing, spigot: die-cast aluminium EN AC 44300, screws treated with Geomet anti-galvanic coating, powder coated texturized light grey (GY), Spigot painted. Via the configurator: Texturized black (BK), Texturized anthracite (ANT) and 48 other RAL possibilities. Standard corrosion class C5 according to ISO 9223: 2012.

Glass: Toughened glass, 4 or 5 mm thickness

Fixings: stainless steel, with anti-galvanic treatment

Installation/Mounting

Installation up to 15 m height

- Versatile tilting technology, lateral ($-15^\circ/+15^\circ$) and post top ($0^\circ/+20^\circ$)
- Adjustable inclination by increments of 5° to optimize lighting distribution and uniformity
- Universal spigot for lateral and post top installation
- As a standard: possible coastal application thanks to its C5 corrosion protection class (ISO 9223:2012)
- Pre-wired for ease of installation at any pole height. Option with IP67 quick connector if pole cable is retained (refurbishment)

Isaro

Ordering Guide

Description	ILCOS Code	Socket	Wt (kg)	SAP Code	Cat. No.
Isaro Extra Small, Narrow road optic					
IS XS 12L70 740 NR CL2 WS8 T60F GY-S	LED		3,63	92938364	E7728384
IS XS 12L35 740 NR CL2 WS6 T60F GY-S	LED		3,38	92938802	E7728385
IS XS 12L35 730 NR CL2 WS6 T60F GY-S	LED		3,38	92938814	E7728397
IS XS 12L50 730 NR CL2 WS8 T60F GY-S	LED		3,63	92938815	E7728398
IS XS 12L70 730 NR CL2 WS8 T60F GY-S	LED		3,63	92938816	E7728399
IS XS 12L50 740 NR CL2 WS8 T60F GY-S	LED		3,63	92957275	E7728696
IS XS 12L25-730 NR CL1 WS0.3 M60 GY-S	LED		3,1	96636129	
IS XS 12L35-730 NR CL1 WS0.3 M60 GY-S	LED		3,1	96636130	
IS XS 12L50-730 NR CL1 WS0.3 M60 GY-S	LED		3,1	96636131	
IS XS 12L70-730 NR CL1 WS0.3 M60 GY-S	LED		3,33	96636132	
IS XS 12L85-730 NR CL1 WS0.3 M60 GY-S	LED		3,33	96636133	
IS XS 12L105-730 NR CL1 WS0.3 M60 GY-S	LED		3,33	96636134	
IS XS 12L25-730 NR CL2 WS0.3 M60 GY-S	LED		3,07	96636147	
IS XS 12L35-730 NR CL2 WS0.3 M60 GY-S	LED		3,07	96636148	
IS XS 12L50-730 NR CL2 WS0.3 M60 GY-S	LED		3,13	96636149	
IS XS 12L70-730 NR CL2 WS0.3 M60 GY-S	LED		3,13	96636150	
IS XS 12L85-730 NR CL2 WS0.3 M60 GY-S	LED		3,13	96636151	
IS XS 12L105-730 NR CL2 WS0.3 M60 GY-S	LED		3,13	96636152	
IS XS 24L25-730 NR CL2 WS0.3 M60 GY-S	LED		3,27	96636336	
IS XS 24L35-730 NR CL2 WS0.3 M60 GY-S	LED		3,27	96636337	
IS XS 24L50-730 NR CL2 WS0.3 M60 GY-S	LED		3,27	96636338	
IS XS 24L70-730 NR CL2 WS0.3 M60 GY-S	LED		3,27	96636339	
IS XS 24L25-730 NR CL1 WS0.3 M60 GY-S	LED		3,3	96636340	
IS XS 24L35-730 NR CL1 WS0.3 M60 GY-S	LED		3,3	96636341	
IS XS 24L50-730 NR CL1 WS0.3 M60 GY-S	LED		3,3	96636342	
IS XS 24L70-730 NR CL1 WS0.3 M60 GY-S	LED		3,3	96636343	
Isaro Small, Narrow road optic					
IS S 24L35 740 NR CL2 WS8 T60F GY-S	LED		4,33	92938803	E7728386
IS S 24L50 740 NR CL2 WS8 T60F GY-S	LED		4,33	92938804	E7728387
IS S 24L50 740 NR ZU CL2 WS8 T60F GY-S	LED		4,48	92938805	E7728388
IS S 24L70 740 NR CL2 WS8 T60F GY-S	LED		4,33	92938806	E7728389
IS S 24L70 740 NR ZU CL2 WS8 T60F GY-S	LED		4,48	92938807	E7728390
IS S 36L50 740 NR CL2 WS8 T60F GY-S	LED		4,67	92938808	E7728391
IS S 36L50 740 NR ZU CL2 WS8 T60F GY-S	LED		4,82	92938809	E7728392
IS S 36L50 740 NR CL2 WS10 T60F GY-S	LED		4,87	92938810	E7728393
IS S 36L50 740 NR ZU CL2 WS10 T60F GY-S	LED		5,02	92938811	E7728394
IS S 36L70 740 NR CL2 WS10 T60F GY-S	LED		4,89	92938812	E7728395
IS S 36L70 740 NR ZU CL2 WS10 T60F GY-S	LED		5,04	92938813	E7728396
IS S 24L35 730 NR CL2 WS8 T60F GY-S	LED		4,33	92938817	E7728400
IS S 24L50 730 NR CL2 WS8 T60F GY-S	LED		4,33	92938818	E7728401
IS S 24L70 730 NR CL2 WS8 T60F GY-S	LED		4,33	92938819	E7728402
IS S 24L50 730 NR ZU CL2 WS8 T60F GY-S	LED		4,48	92938820	E7728403
IS S 24L70 730 NR ZU CL2 WS8 T60F GY-S	LED		4,48	92938821	E7728404
IS S 24L35 730 NR ZU CL2 WS8 T60F GY-S	LED		4,48	92938822	E7728405
IS S 36L50 730 NR ZU CL2 WS8 T60F GY-S	LED		4,82	92938823	E7728406

Isaro

Description	ILCOS Code	Socket	Wt (kg)	SAP Code	Cat. No.
IS S 36L50 730 NR CL2 WS8 T60F GY-S	LED		4,67	92938824	E7728407
IS S 36L70 730 NR CL2 WS10 T60F GY-S	LED		4,89	92938825	E7728408
IS S 36L70 730 NR ZU CL2 WS10 T60F GY-S	LED		5,04	92938826	E7728409
IS S 24L25-730 NR CL1 WS0.3 M60 GY-S	LED		4,03	96636135	
IS S 24L35-730 NR CL1 WS0.3 M60 GY-S	LED		4,03	96636136	
IS S 24L50-730 NR CL1 WS0.3 M60 GY-S	LED		4,03	96636137	
IS S 24L70-730 NR CL1 WS0.3 M60 GY-S	LED		4,03	96636138	
IS S 24L85-730 NR CL1 WS0.3 M60 GY-S	LED		4,06	96636139	
IS S 24L105-730 NR CL1 WS0.3 M60 GY-S	LED		4,06	96636140	
IS S 36L25-730 NR CL1 WS0.3 M60 GY-S	LED		4,1	96636141	
IS S 36L35-730 NR CL1 WS0.3 M60 GY-S	LED		4,1	96636142	
IS S 36L50-730 NR CL1 WS0.3 M60 GY-S	LED		4,37	96636143	
IS S 36L70-730 NR CL1 WS0.3 M60 GY-S	LED		4,37	96636144	
IS S 36L85-730 NR CL1 WS0.3 M60 GY-S	LED		4,6	96636145	
IS S 36L105-730 NR CL1 WS0.3 M60 GY-S	LED		4,6	96636146	
IS S 24L25-730 NR CL2 WS0.3 M60 GY-S	LED		4	96636153	
IS S 24L35-730 NR CL2 WS0.3 M60 GY-S	LED		4	96636154	
IS S 24L50-730 NR CL2 WS0.3 M60 GY-S	LED		4	96636155	
IS S 24L70-730 NR CL2 WS0.3 M60 GY-S	LED		4	96636156	
IS S 24L85-730 NR CL2 WS0.3 M60 GY-S	LED		4,03	96636157	
IS S 24L105-730 NR CL2 WS0.3 M60 GY-S	LED		4,03	96636158	
IS S 36L25-730 NR CL2 WS0.3 M60 GY-S	LED		4,06	96636159	
IS S 36L35-730 NR CL2 WS0.3 M60 GY-S	LED		4,06	96636160	
IS S 36L50-730 NR CL2 WS0.3 M60 GY-S	LED		4,34	96636161	
IS S 36L70-730 NR CL2 WS0.3 M60 GY-S	LED		4,34	96636162	
IS S 36L85-730 NR CL2 WS0.3 M60 GY-S	LED		4,57	96636163	
IS S 36L105-730 NR CL2 WS0.3 M60 GY-S	LED		4,57	96636164	
Isaro with Zhaga socket, 3000K					
IS XS 12L50-730 NR2 M CLO BP3550 ZU ->	LED		3,83	92945455	
IS XS 12L70-730 ENR M CLO BP3550 ZU ->	LED		3,83	92945456	
IS S 24L50-730 NR M CLO BP3550 ZU CL2 ->	LED		4,54	92945457	
IS S 24L70-730 NR M CLO BP3550 ZU CL2 ->	LED		4,54	92945458	
IS S 36L70-730 NR M CLO BP3550 ZU CL2 ->	LED		5,085	92945459	
IS S 36L105-730 MR M CLO BP3550 ZU ->	LED		5,305	92945460	
IS XS 12L70 730 ENR M CLO ZU CL2 WS3 ->	LED		3,24	92945461	