



Contus

CONTUS Trunking System

- Energy-efficient LED continuous row luminaire with light efficiency of up to 163 lm/W
- Provides optimal linear illuminance for your application area, such as Retail, Logistics & Industry, with a choice of 4 beam angles; Wide Beam, Very Wide Beam, Narrow Beam and Shelf Beam
- Colour tolerance between several luminaires of max. 3 MacAdam ellipses
- LED Service life: up to L80 at 50.000h
- Phase selection for 3 phase circuits and 2 emergency lighting circuits
- 100 % flexible, tool-free mechanical and electrical installation via the two side-mounted rotary levers



Photographs, line drawings and photometric data are representative only. For specific product detail please select an individual product.



92979270

Material/Finish

Trunking units: pre-coated roll form steel, white (similar to RAL9016)

Electrical feeds: pre-coated roll form steel, white (similar to RAL9016), combined with galvanised steel mechanical connector

Battens: pre-coated roll form steel, white (similar to RAL9016)

End caps: Polycarbonate for Trunking, Acrylonitrile styrene acrylate for Battens

Mounting accessory: Stainless steel wall/ceiling mount components

Diffuser/Lens: injection moulded PMMA Plastic

Installation/Mounting

CONTUS continuous-row lighting system can be installed without the need for tools. Thanks to a unique, factory mounted connector, the trunking units can be connected mechanically and electrically at the same time. Luminaires simply lock into place and can be repositioned easily at any time.

An easy to use mounting bracket provides the connection between the wall or ceiling and the trunking. A cord suspension can be fixed to the trunking without the use of any tool by exerting slight pressure, and it can also be moved as required. Pendant height adjustment is also entirely tool-free. The distance between the suspension points can be up to 3 meters. The system can be installed in an environment with ambient temperatures of -10°C up to +35°C degrees for HE luminaires and -10°C up to +30°C degrees for HO luminaires.

Contus

Ordering Guide

Description	ILCOS Code	Socket	Wt (kg)	SAP Code	Cat. No.
Contus, batten, length 1000mm					
CONTUS 3700-840 L1000 WB HF WH	LED	LED	1,43	96635806	
CONTUS 5200-840 L1000 WB HF WH	LED	LED	1,43	96635807	
CONTUS 3700-840 L1000 WB HFIX WH	LED	LED	1,5	96635812	
CONTUS 5200-840 L1000 WB HFIX WH	LED	LED	1,5	96635813	
CONTUS 5200-840 L1000 NB HF WH	LED	LED	1,425	96635818	
CONTUS 5200-840 L1000 SB HF WH	LED	LED	1,425	96635819	
CONTUS 5200-840 L1000 VWB HF WH	LED	LED	1,435	96635820	
CONTUS 5200-830 L1000 WB HF WH	LED	LED	1,43	96636073	
Contus, batten, length 1500mm					
CONTUS 5500-840 L1500 WB HF WH	LED	LED	2,13	96635808	
CONTUS 8000-840 L1500 WB HF WH	LED	LED	2,13	96635809	
CONTUS 5500-840 L1500 WB HFIX WH	LED	LED	2,2	96635814	
CONTUS 8000-840 L1500 WB HFIX WH	LED	LED	2,2	96635815	
CONTUS 8000-840 L1500 NB HF WH	LED	LED	2,12	96635821	
CONTUS 8000-840 L1500 SB HF WH	LED	LED	2,12	96635822	
CONTUS 8000-840 L1500 VWB HF WH	LED	LED	2,14	96635823	
CONTUS 8000-830 L1500 WB HF WH	LED	LED	2,13	96636074	
Contus, batten, length 2000mm					
CONTUS 7400-840 L2000 WB HF WH	LED	LED	2,755	96635810	
CONTUS 10000-840 L2000 WB HF WH	LED	LED	2,755	96635811	
CONTUS 7400-840 L2000 WB HFIX WH	LED	LED	2,825	96635816	
CONTUS 10000-840 L2000 WB HFIX WH	LED	LED	2,825	96635817	
CONTUS 10000-840 L2000 NB HF WH	LED	LED	2,74	96635824	
CONTUS 10000-840 L2000 SB HF WH	LED	LED	2,74	96635825	
CONTUS 10000-840 L2000 VWB HF WH	LED	LED	2,77	96635826	
CONTUS 10000-830 L2000 WB HF WH	LED	LED	2,755	96636075	
Contus, trunking units					
CONTUS T L1500 WH			2,9	96635827	
CONTUS T L2000 WH			3,7	96635828	
CONTUS T L2500 WH			4,49	96635829	
CONTUS T L4000 WH			6,6	96635830	
Contus, electrical feed					
CONTUS TA WH			0,56	96635831	
CONTUS TA-F WH			2,04	96635832	
CONTUS TE L500 WH			1,4	96635833	
CONTUS TM TA/TE L500 WH			1,3	96635834	
CONTUS TM L750 WH			1,45	96635835	
CONTUS TE WH			0,7	96636186	
Contus, node connector					
CONTUS T-VL1 WH			1,35	96635838	
CONTUS T-VL2 WH			1,84	96635839	
CONTUS T-VL3 WH			1,7	96635840	

Contus

Description	ILCOS Code	Socket	Wt (kg)	SAP Code	Cat. No.
CONTUS T-VL4 WH			1,88	96635841	
CONTUS T-VT1 WH			2,1	96635842	
CONTUS T-VT2 WH			2,42	96635843	
CONTUS T-VT3 WH			2,9	96635844	
CONTUS T-VT4 WH			2,42	96635845	
Contus, mounting components					
TECTON/CONTUS/SLN2/SLOIN/SLOT2/EQL A			0,2	22169175	
TECTON/CONTUS AC (Caddy Clip)			0,026	22169176	
TEC/CONT/SLN2/SLOIN/EQL/CHAL3 ASI1 O-L			0,07	22169178	
TEC/CONT/SLN2/SLOIN/EQL/CHAL3 ASI2 O-L			0,8	22169179	
TECTON/CONTUS ASI5 O-L			0,08	22169180	
TECTON/CONTUS ASI1 O-L + Caddy-Clip			0,071	22169181	
TECTON/CONTUS ASI2 O-L + Caddy-Clip			0,1	22169182	
TECTON/CONTUS ASI1 O-L LOOP			0,08	22170952	
TECTON/CONTUS ASI2 O-L LOOP			0,09	22170954	
TECTON/CONTUS ASI5 O-L LOOP			0,13	22170956	
TECTON/CONTUS AK			0,05	22169177	
SWI 2.5 1000 CHAIN ST/ZN #K27 KNOTTED			0,13	20042906	
ZAKK NIRO (K27 KNOTENKETTE 1.43)			0,158	20969682	
Contus, cover strip					
TECTON/CONTUS T/KK AK 1498 PP WH			0,1	22170178	
TECTON/CONTUS T/KK AK 1997 PP WH			0,14	22170180	
Contus, accessories					
TECTON/CONTUS TZ			0,073	22161459	
TECTON/CONTUS T-EF WH			0,1	22065758	
TECTON/CONTUS ABLH			0,675	22064924	